

Technical data sheet
PLUS 760
Antisilicone additive

PROPERTIES	
PLUS 760 ANTISILICONE ADDITIVE – an agent that prevents pinholes which occur after contamination of surfaces with silicone or by greasing. If pinholes appear on the first paint coating, apply the second with PLUS 760.	
APPLICATION:	
Novol acrylic clearcoats and acrylic topcoats.	
MIXING RATIO	
Use the PLUS 760 antisilicone additive depending on the contamination severity from 2 to 4% on the ready to use mixture of the clearcoat/topcoat and hardener. Example: with 2% per 1 litre of mixture, add 20 ml of PLUS 760.	
SPRAY VISCOSITY	
Adding PLUS 760 does not affect the product's spray viscosity.	
COLOUR	
Colourless	
STORAGE CONDITIONS	
Store in a cool dry room, away from sources of fire and heat. Avoid direct exposure to sunlight.	
SHELF LIFE	
PLUS 760	24 months/20°C
SAFETY	
See Safety Data Sheet.	
OTHER INFORMATION	
The effectiveness of our systems results from laboratory research and many years of experience. The data contained herein meets the current knowledge about our products and their application potential. We ensure high quality, provided the user follows the instructions and the work is performed in accordance with good workmanship. It is necessary to do a test application of the product due to its potentially different reaction with different materials. We may not be held liable for defects if the final result was affected by factors beyond our control.	